








PRODUCT	ECS-327SMO	ECS-8F	ECS-3951C/3953C	ECS-3955C
PRODUCT ILLUSTRATION				
FREQUENCY RANGE	32.768 KHz	1.0 ~ 80.000 MHz	1.8 MHz ~ 80 MHz	1.8 ~ 66.666 MHz
FREQUENCY STABILITY	-60/+30 PPM	±100 PPM	±100 PPM	±100 PPM
TEMPERATURE RANGE	-10 ~ +60°C	-10 ~ +70°C	0 ~ +70°C	0 ~ +70°C
FEATURES	<ul style="list-style-type: none"> • 4 x 6.5 mm Footprint • HCMOS • 3.3 V Version 	<ul style="list-style-type: none"> • HCMOS/TTL • 55/45 Symmetry • Tri-State, EN/DS • Extended Temp Range • 3V & 5V Versions 	<ul style="list-style-type: none"> • HCMOS/TTL • 1.6 mm Profile • ±50 & ±30 PPM Options • Ceramic Package • Tri-State • 3V & 5V Versions 	<ul style="list-style-type: none"> • HCMOS/TTL • High Output Load • ±50 & ±30 PPM Options • 1.6 mm Profile • Multi-Volt Versions • Tri-State
PAGE #	40	41	42	43

PRODUCT	ECS-3951M/3953M	ECS-3955M	ECS-3961/3963
PRODUCT ILLUSTRATION			
FREQUENCY RANGE	1.8 ~ 125 MHz	1.8 ~ 70 MHz	2.5 ~ 66.666 MHz
FREQUENCY STABILITY	±100 PPM	±100 PPM	±100 PPM
TEMPERATURE RANGE	-10 ~ +70°C	-10 ~ +70°C	-10 ~ +70°C
FEATURES	<ul style="list-style-type: none"> • HCMOS/TTL • ±50 & ±30 PPM Options • 1.6 mm Profile • Tri-State • 3V & 5V Versions • Seam Welded Package 	<ul style="list-style-type: none"> • HCMOS/TTL • High Outout Load • ±50 & ±30 PPM Options • 1.6 mm Profile • Tri-State • 3V & 5V Versions 	<ul style="list-style-type: none"> • HCMOS/TTL • ±50 & ±30 PPM Options • 1.0 mm Profile • Tri-State • 3.2 x 5 mm Footprint • 3V & 5V Versions
PAGE #	44	45	46