

PRODUCT	THRU-HOLE MONOLITHIC CRYSTAL FILTERS (MCF)	ECS-96SMF SMD MCF	LTM450 & 455 KHz CERAMIC BPF'S	LTE SERIES CERAMIC BPF'S
PRODUCT ILLUSTRATION				
FREQUENCY RANGE	10.7 ~ 90 MHz	21.4 ~ 109.65 MHz	450 ~ 459 KHz	4.5 ~ 6.5 MHz
TEMPERATURE RANGE	-20 ~ +70°C	-30 ~ +85°C	-	-
FEATURES	<ul style="list-style-type: none"> • High Stability • Compact Package Size • Narrow & Intermediate Bandwidth Options • 2 ~ 10 Pole Response's 	<ul style="list-style-type: none"> • SMD MCF • 1.5 mm Profile • 2 Pole Response • 5 x 7 mm Footprint • Tape & Reel 	<ul style="list-style-type: none"> • Ultra Small Size • 2, 4, & 6 Element • Cost Effective • Wide Range of Bandwidths available 	<ul style="list-style-type: none"> • Wide Bandwidths • Low Insertion Loss • TV SIF Stage • Excellent Spurious Suppression Characteristics
PAGE #	74-76	77	78-82	83

PRODUCT	XT SERIES CERAMIC TRAP	L10.7 SERIES CERAMIC BPF'S	ECS-D479.5B/D480A SERIES SAW FILTER	ECS-DSF400.0A-51/DSF947.5B-21 SAW FILTER
PRODUCT ILLUSTRATION				
FREQUENCY RANGE	4.5 ~ 6.5 MHz	10.64 ~ 10.76 MHz	479.5 & 480 MHz	400 & 947.5 MHz
TEMPERATURE RANGE	-	-	-25 ~ +85°C	-
FEATURES	<ul style="list-style-type: none"> • TV Ceramic Trap • Excellent Spurious Suppression Characteristics • Low Insertion Loss 	<ul style="list-style-type: none"> • Wide Bandwidths • Low Insertion Loss • IF Filter • Cost Effective 	<ul style="list-style-type: none"> • Wide Bandwidths • TO-39 Package • Cost-Effective 	<ul style="list-style-type: none"> • SMD Package • Cost-Effective
PAGE #	84	85	86	87